


A-1200

Rod Control Swinghandle



IP65



NEW



选型 Model selection

A-1200-10YZ-333-42

1. 帶防尘盖: With Dustcap
2. 不带防尘盖: Without Dustcap

1. 帶挂: with padlock
2. 不帶挂: without padlock

42: 粉末涂层砂纹黑

42: Powder-coated sand texture black

A1 代表 SUS304

A1 represents SUS304

333.K333 钥匙 K333 Key

014. 双翅 4mm Double Bit 4mm

037: 三角 7mm 7mm Triangle

047: 四方 7mm 7mm Square-shaped

- 10: Version A(锁舌型 Cam control)
20: Version B(两点拉杆型 2P.rod control)
30: Version C(三点拉杆型 3P.rod control)

1. Material and surface treatment:
Lock body, handle, dust cover : SUS304
Steel bolt: SUS304
Sealing ring: EPDM foam.

2. Performance parameters:
Protection class: IP65
Handle bearing tension value: $\leq 400\text{N}$
Handle bearing torque value: $\leq 35\text{N}\cdot\text{m}$

3. Remarks:
Default Keyed K333

- 1.材质及表面处理:
锁体,手柄,防尘盖: SUS304
钢栓: SUS304
密封圈: EPDM发泡胶。

- 2.性能参数:
防护等级: IP65
手柄承载拉力值: $\leq 400\text{N}$
手柄承载扭矩值: $\leq 35\text{N}\cdot\text{m}$

- 4.备注:
默认K333钥匙