









C6-1511 compression cam latch

RL

IP65

SS316 SERIES







锁芯 Cylinder



237 238

选型 Model selection

锁芯选型
Lock cylinder selection

A1 代表 SUS304
A1 represents SUS304
A2 代表 SUS316
A2represents SUS316

C6-1511-SX-LH-30L

L 代表钢栓长度
L represents the length of the steel bolt
H 代表有效高度
H represents effective height

旋转 Rotate



顺时针锁紧
Clockwise locking

逆时针锁紧
Lock counterclockwise

1.Material and surface treatment:
Main body : Zamak DIN-EN 1774-ZnAl4Cu1
Steel bolt: iron galvanized

2. Performance parameters:
Protection class: IP65
Unlocking torque: ≤ 0.79N/M
Ultimate load: 700N
Tensioning and stretching amount: 7mm

3. Installation instructions:
Fixed screw torque 8N. M
Fixed nut torque 17N. M
Applicable door panel thickness: 1-5mm

1.材质及表面处理:
主体 :5#锌合金
钢栓：铁镀锌
密封圈：EPDM发泡胶。

2.性能参数:
防护等级：IP65
解锁扭矩：小于等于 0.79N/M
极限载荷：700N
拉紧伸缩量：4mm

3.安装说明:
固定螺丝扭矩 8N.M
固定螺母扭矩 17N.M

如需获得产品3D模型图，请联系 WWW.FORNDLOCK.COM